



BIG BLUE™

SUBMITTAL AND DATA SHEET

PIPE SIZE (IN)	AVERAGE O.D. (IN)	NOM. I.D. (IN)	MIN. T. (IN)	MIN. E (IN)	APPROX. D ⁹ (IN)	APPROX. WEIGHT (LBS/FT)
Rated 235 psi (DR 18)						
14	15.30	13.50	0.850	8.00	19.00	26.75
16	17.40	15.35	0.967	9.25	21.62	34.86
18	19.50	17.20	1.083	13.00	24.22	48.95
20	21.60	19.06	1.200	14.50	26.85	54.22
24	25.80	22.76	1.433	12.00	32.06	77.97
Rated 200 psi (DR 21)*						
14	15.30	13.75	0.729	8.00	18.22	23.07
16	17.40	15.64	0.829	9.25	20.72	30.04
18	19.50	17.53	0.929	13.00	23.22	37.27
20	21.60	19.42	1.029	14.50	25.72	46.71
24	25.80	23.19	1.229	12.00	30.72	67.53
30	32.00	28.77	1.524	16.75	38.10	103.71
36	38.30	34.43	1.824	19.02	45.60	152.16
Rated 165 psi (DR 25)						
14	15.30	14.00	0.612	8.00	17.94	19.48
16	17.40	15.92	0.696	9.25	20.41	25.38
18	19.50	17.85	0.780	13.00	22.87	31.99
20	21.60	19.77	0.864	14.50	25.34	39.46
24	25.80	23.61	1.032	12.00	30.27	56.98
30	32.00	29.29	1.280	16.75	37.12	88.49
36	38.30	35.05	1.532	19.02	44.43	128.41
42	44.50	40.73	1.780	22.43	51.62	176.02
48*	50.80	46.49	2.032	24.78	58.93	231.22
Rated 125 psi (DR 32.5)*						
14	15.30	14.30	0.471	8.00	17.48	15.14
16	17.40	16.27	0.535	9.25	19.88	19.63
18	19.50	18.23	0.600	13.00	23.30	24.75
20	21.60	20.19	0.665	14.50	24.38	30.54
24	25.80	24.12	0.794	12.00	29.47	44.11
30	32.00	29.91	0.985	16.75	35.94	68.45
36	38.30	35.80	1.178	19.02	43.01	99.22
42	44.50	41.60	1.369	22.43	49.98	135.49
48	50.80	47.49	1.563	24.78	56.73	178.49




Building essentials
for a better tomorrow™



PIPE SIZE (IN)	AVERAGE O.D. (IN)	NOM. I.D. (IN)	MIN. T. (IN)	MIN. E (IN)	APPROX. D ⁹ (IN)	APPROX. WEIGHT (LBS/FT)
Rated 100 psi (DR 41)						
14	15.30	14.52	0.37	8.00	16.07	12.01
16	17.40	16.51	0.42	9.25	18.28	15.63
18	19.50	18.50	0.47	13.00	20.49	19.72
20	21.60	20.49	0.52	14.50	22.70	24.31
24	25.80	24.48	0.62	12.00	27.11	35.10
30	32.00	30.35	0.78	16.75	35.12	54.65
36	38.30	36.30	0.93	19.02	42.04	78.97
42	44.50	42.18	1.08	22.43	48.84	108.19
48	50.80	48.14	1.23	24.78	55.76	142.10
Rated 80 psi (DR 51)**						
18	19.50	18.69	0.382	11.09	20.30	15.92
24	25.80	24.72	0.506	14.90	26.86	28.39
30	32.00	30.67	0.627	16.75	34.50	44.08
36	38.30	36.71	0.751	19.02	41.30	64.32
42	44.50	42.65	0.872	22.43	47.99	88.10
48	50.80	48.69	0.996	24.78	54.78	115.79

* Prior to ordering or specifying, consult JM Eagle™ for product and/or listing availability.

** UL 1285 up to 24"



I.D. : Inside Diameter
 O.D. : Outside Diameter
 T. : Wall Thickness
 D⁹ : Bell Outside Diameter
 E : Distance between Assembly Mark to the end of spigot.

- Product Standard: ANSI/AWWA C905
- Pipe Compound: ASTM D1784 Cells Class 12454
- Gasket: ASTM F477
- Integral Bell Joint: ASTM D3139
- Certifications: ANSI/NSF Standard 61
UL Standard 1285
- Pipe Length: 20 feet laying length
- Installation: AWWA C605
JM Eagle™ Installation Guide