M&H AWWA LARGE RESILIENT WEDGE GATE VALVES

SPECIFICATIONS / AVAILABLE CONFIGURATIONS & STYLE NUMBERS (14"-24")

Size Range	Water Working	Bubble Tight Seat	Hydrostatic Shell
	Pressure psi	Test psi	Test psi
AWWA 14" – 24"	200	200	400

SIZE RANGE / STYLE NUMBER / STANDARD--Non Geared

	Size	Style No. With	Style No. With	Style No. With
	Range	2" Nut	Hand wheel	Post Plate
Mechanical Joint	14"-16"	4067-01	4067-01HW	4067-01P
Flanged Ends	14"-16"	4067-02	4067-02HW	4067-02P
Mechanical Joint X Flange	14"-16"	4067-13	4067-13HW	4067-13P
Tapping Valve	14"-16"	4751-01	4751-01HW	4751-01P
Push On (For Ductile Iron / C900)	16"	4067-22	4067-22HW	4067-22P
OS&Y	14"-16"		4068	

SIZE RANGE WITH SPUR GEAR OPERATOR (NRS or OS&Y)

Mechanical Joint (With Spur Gears)	14"-24"
Flanged Ends (With Spur Gears)	14"-24"
Mechanical Joint X Flange (With Spur Gears)	14"-24"
Tapping Valve (With Spur Gears)	14"-24"

SIZE RANGE WITH BEVEL GEAR OPERATOR (NRS or OS&Y)

Mechanical Joint X Flange (With Bevel Gears)	14"-24"
Flanged Ends (With Bevel Gears)	14"-24"
Tapping Valve (With Bevel Gears)	14"-24"
Mechanical Joint (With Bevel Gears)	14"-24"
Push On (For Ductile Iron / C900)	16"

NOTES: 14" size and larger are not UL Listed / FM Approved

18", 20", 24" valves require either spur gears or bevel gears.

BY-Pass valve not required on 14" – 24" RW Valves

VALVE ACCESSORIES

Mechanical operational accessories are used for valves having special operational needs such as;

- 1. Location with limited access
- 2. Hazardous locations
- 3. Revision of operational position
- 4. High Torque Operation
- 5. Indication of Valve Position

Accessory selection must be evaluated for its capability to transmit the required torque requirements to the valve. To assure long-term trouble free operation, its materials of construction should take into account factors relating to corrosion and maintenance.

Accessories used on M&H valves can include the following:

Electric Motor Operators Stem Guides Indicator Posts Hand wheels "T" Handles Extension Stems

Floor Boxes Chain Wheels Floor stands (Non-rising stem)

Position Indicators Miter Box Gearing Electronic Switches

July 2005 / Large RW Gate Valves 14" to 24"